

Product information

PowerPozz™ white

**Thermal treated pure kaolin (metakaolin)
pozzolanic hardening admixture for cementitious building materials**

Description

PowerPozz™ white is produced by calcination of purified kaolin and is a white, mostly amorphous aluminosilicate reacting with Portlandite (calcium hydroxide) to build cementitious CSH-phases.

PowerPozz™ conforms to ASTM C-618 (Specifications for Natural and Calcined Pozzolans)

Chemical composition (M.-%)

SiO ₂	54-56	CaO	< 0,1	SO ₃	< 0,05
Al ₂ O ₃	40-42	MgO	< 0,1	P ₂ O ₅	< 0,2
Fe ₂ O ₃	< 1,4	Na ₂ O	< 0,05		
TiO ₂	< 3,0	K ₂ O	< 0,4	LOI	< 1,0

Physical characteristics

Specific density		2,6	g/cm ³
Particle size distribution	D 10	~ 2	µm
	D 50	~ 5	µm
	D 90	~ 25	µm
Specific surface (Blaine)		ca. 26 000	cm ² /g
Specific surface (BET)		ca. 20	m ² /g
Colour		white	
Whiteness (Dr. Lange)		ca. 77	
Apparent density	freely settled	0,3 – 0,4	g/cm ³
	tapped	ca. 0,5	g/cm ³

Function

PowerPozz™ is mostly composed of the mineral Kaolinit – a layered silicate mineral with a distance of 7,2 Å between the layers. Between the layers of SiO₂ and Al₂O₃ in proportions of 1:2 water is imbedded in the layers that can be evaporated through heat treatment by calcination. The kaolin is then activated.

Portland cement develops 25 % calcium hydroxide (free lime) in its hydration. This alkaline by-product is very soluble and is primarily attacked and dissolved in the presence of acids or sulphates.

PowerPozz™ special feature is its capacity to bind large amount of free lime in the form of stable CSH-phases. Speed and amount of this reaction may be controlled through chemical and construction adequate methods

In relation to its reactivity PowerPozz™ can be qualified as „rapid“. Together with lime and water the setting will occur in about 7 hours (method Newchem).

Application

PowerPozz™ is a pozzolanic mineral additive that may improve many performances of hydraulic cementitious mortars, concrete and analogous products.

PowerPozz™ is easily mixed in and gives a soft plastic consistence that is easy to work (buttery effect).

PowerPozz™ has shown its advantages in applications where strength, density and resistance are requested. Because of the finesse, high specific surface and reactivity it is well suited to replace silica fume.

In the following applications PowerPozz™ has been shown to be very useful:

Plasticity	shot-creet, repair mortars, coatings
Stability	self compacting mortar and concrete, selfleveling compounds
Strength	high performance concrete (HPC) or mortars (HPM)
Lime binding	tile adhesive, coating of water pipes, precast
Resistance	coatings of waste water or see water constructions
Pigmentation	better dispersion in precast or visible concrete
Efflorescence	roofing tiles, facade precast
Durability	improved alkali silicate reaction

Dosage 5 to 15 % replacement of cement by weight.

Stability unlimited in dry conditions.

Storage in protected and dry rooms.

Packaging in bags of 20 kg or in big bags of 1000 kg.

The above information and recommendations are based upon our experience and are offered merely for advice. They do not absolve the consumer from making his own tests. Responsibility for damage arising from the use of our products cannot be derived from the recommendations given. The observance of any intellectual property rights of third parties is the responsibility of the consumer in each case.

PInfo PPw 2007-07 – v5e