

## **Product information**

## Metaver® K

# Metakaolin - pozzolanic hardening admixture for hydraulic building materials

#### **Description**

Metaver® K is produced by calcination of concentrated kaolin and is a mostly amorphous aluminium silicate reacting with Portlandite (calcium hydroxide) to build cementitious CSH-phases.

## Chemical composition (M.-%, approx.)

SiO <sub>2</sub>	53 - 54
$Al_2O_3$	41 - 44
Fe <sub>2</sub> O <sub>3</sub>	< 1,2
K <sub>2</sub> O	< 1,3

#### Physical characteristics (approx.)

Appearance:

Colour grey

Specific density 2,6 g/cm<sup>3</sup>

Bulk density 380 - 520 kg/m<sup>3</sup>

Particle size distribution  $d_{50}$  6  $\mu m$   $d_{90}$  17  $\mu m$ 

## **Function**

Portland cement develops ca. 25 % calcium hydroxide (free lime) in its hydration. This alkaline by-product is very soluble and is primarily attacked and dissolved in the presence of acids or sulphates.

Metaver® K special feature is its capacity to bind large amount of free lime in the form of stable CSH-phases. Reactivity and amount of this reaction may be controlled through chemical and construction adequate methods.

In relation to its reactivity Metaver® K can be qualified as "medium".



#### **Application**

Metaver® K is a pozzolanic mineral additive that may improve many performances of hydraulic cementitious mortars, concrete and analogous products.

Metaver® K I is easily mixed in. It gives a soft plastic consistence with good workability in the final product. Through its particle size distribution, no big increase in water demand is given.

Metaver® K has shown its advantages in applications where strength, density and resistance are requested.

Metaver® K is approved for usage in concrete according to NF 18-513.

In the following applications Metaver® K has been shown to be very useful:

Plasticity shotcrete, repair mortars, coatings

Stability self-compacting concrete and mortars, selfleveling compounds

Strength renders based on lime and cement

Lime binding tile adhesive, coating of water pipes and reservoirs Resistance coatings of waste water or sea water constructions Pigmentation better dispersion in precast or visible concrete

Efflorescence roofing tiles, facade precast Durability reduced alkali silicate reaction

**Dosage** 

5 to 15 % replacement of cement by weight.

**Stability** 

Unlimited in dry conditions.

**Storage** 

In protected and dry rooms.

**Packaging** 

In 25 kg bags or big bags of 1000 kg.

The above information and recommendations are based upon our experience and are offered merely for advice. They do not absolve the consumer from making his own tests. Responsibility for damage arising from the use of our products cannot be derived from the recommendations given. The observance of any intellectual property rights of third parties is the responsibility of the consumer in each case.

MDS Metaver® K 2019